UNITED STATES PATENT APPLICATION FOR

A1

SYSTEM AND METHOD OF LINKING WIRELESS SIGNALLING PROTOCOL WITH MEDIA GATEWAY CONTROL PROTOCOL IN PACKET BASED NETWORK

INVENTORS:

Ki-Hyun Joo

Chol Su Kang

Sung Goo Shim

Jay Wu Hong

SYSTEM AND METHOD OF LINKING WIRELESS SIGNALLING PROTOCOL WITH MEDIA GATEWAY CONTROL PROTOCOL IN PACKET BASED NETWORK.

FIELD OF THE INVENTION

The present claimed invention relates generally to the field of wireless communication systems. More particularly, the present claimed invention relates to packet based wireless base stations which interface with Call Agents using wireless signaling protocol for call signaling and Media Gateway Control Protocol for media gateways.

BACKGROUND ART

Local area networks such as Ethernet are well known. Most local area networks are wired, so that each station is connected directly or indirectly to all other stations by cabling or wires, thus providing full connectivity between all stations. Such local area networks avoid collisions and achieve efficient use of the communications channel by well known carrier sensing and collision avoidance schemes. Such schemes are typically not suitable for wireless networks. Communication systems that utilize coded communication signals are well known in the art. One such system is a code division multiple access (CDMA) cellular communication system such as set forth in the Telecommunications Industry Association/Electronic Industries Association International Standard (TIA/EIA IS-95), hereinafter referred to as IS-95.

In accordance with the IS-95, the coded communication signals used in CDMA systems comprise CDMA signals that are transmitted in a common 1.25MHZ bandwidth to base stations of the system from mobile or wireless

communication units, such as cell phones or portable wireless computers or wireless handheld devices, that are communicating in a specific coverage area of the base station. In conventional CDMA systems, the base station communicates with a base station controller which allows the communication unit to communicate with other communication units within the same coverage area. Each CDMA signal includes a pseudo-noise (PN) sequence associated with a particular base station and an identification number of a communicating communication unit.

Typically, the base station controller is connected to a mobile switching controller (MSC) which allows a base station to connect with other base stations outside its coverage area in order to allow a communicating communication unit communicated with other units outside its coverage area.

Figure 1 is an illustration of a conventional prior art CDMA system. In the system shown in Figure 1, the base station 110 and 120 are connected to a base station controller 130 and a mobile switching controller 140 which is in turn connected to the public switched telephone network (PSTN) 150 using known techniques.

In the system shown in Figure 1, when a communication unit initiates a call sequence to either one of the base stations 110 and 120 within a coverage area, an end-to-end connection is established between the respective base stations, the base station controller 130 and the MSC 140using known CDMA call setup techniques. The base stations 110 and 120 typically communicates with the BSC 130 and the MSC 140 via communication links, such as a T1 connection. Base stations 110 and 120 typically have antennas to define the coverage area

within which either base stations primarily accommodate the communication units.

With the proliferation of wireless devices in the office and school environment, the communication system shown in Figure 1 can be very expensive if implemented in an office or in-building environment. The system in Figure 1 also has the inherent problem of wireless voice and data signal quality degradation if implemented in an in-building environment.

To alleviate the problems of the system shown in Figure 1 and with the advent of enterprise based wireless networks, some prior art CDMA systems implement the system shown in Figure 2. In the system illustrated in Figure 2, a wireless base station is connected to existing ethernet network infrastructure to enable the CDMA system utilize existing internet protocol techniques to allow communication between wireless devices connected to the ethernet network.

The system in Figure 2 utilizes a combination of wireless signaling protocol and media gateway protocol to allow wireless call handling and other multi-media data transmission. A wireless signaling protocol is necessary in order to handle mobile terminals.

Despite the robustness of the system in Figure 2 in an in-building wireless environment, there are some disadvantages which characterized such system. First, the system in Figure 2 uses a combination of wireless signaling protocol and media gateway control protocol (MGCP). A wireless signaling protocol is necessary in order to handle mobile terminals and current MGCP protocol assumes that the mobile terminal is wired (at least fixed for the duration of a

call). Hence, mobile terminal signaling can not be sufficiently processed using MGCP protocol alone.

Second, the system requires two different protocols to handle wireless voice communication and other media communication. Whereas a signaling gateway can handle wireless communication, a media gateway cannot handle such typical wireless functions such as location registration of a mobile terminal, paging a mobile terminal, processing handoff of mobile terminals from one base station to another during a conversation in the MGCP protocol.

Thus, the system in Figure 2 requires the base station to have two functional protocol units to handle wireless signaling and multi-media transactions. Traditionally in the wireless network, an open interface specification is defined between base stations and mobile switching centers (MSC). The MSC is a Call Agent like entity to handle the mobile terminal signaling. In CDMA wireless network, EIA/TIA –634 specification defines the interface.

On the other hand, EIA/TIA –634 specification does not define the media control of the IP LAN. Because the EIA/TIA –634 specification assumes the circuit based network, the media identifier is specified in terms of TDM circuit ID of a trunk line between a base station and the MSC. Thus, the wireless signaling protocol is also not sufficient to control the packet based media stream on an IP LAN.

In order to handle both wireless mobile terminal signaling and also media traffic of the wireless mobile terminal, it is necessary for the system in Figure 2 to

support both wireless signaling protocol as well as IP media control protocol. For example, in a CDMA network, EIA/TIA –634 and MGCP can be used for such purpose.

In the example illustrated in Figure 2, the protocol interfaces between a Call Agent and a base station are based on a packet based IP LAN. In the example illustrated in Figure 2, a problem typically arises when the wireless signaling protocol and the media gateway controlling protocol are used together between a Calll Agent and a base station. A linkage (or mapping) between a calll identifier in the wireless signaling protocol and a call identifier of the corresponding call for the same mobile terminal must be made dynamically during each call setup. Because mobile terminals tend to move around within a particular call coverage area, a system mapping of call identifiers statically for a given terminal by a base station is not economically feasible.

Furthermore, EIA/TIA – 634 protocol does not have a method to specify the traffic path on IP LAN associated with a particular signaling call that it is handling. In a conventional circuit based network, EIA/TIA –634 uses 16 bit identification typically known as Circuit Identity Code (CIC) which defines PCM multiplexer id to handle traffic path for a signaling call associated with it. However, this is not adequate for the traffic path on IP LAN because PCM multiplexer is not present on IP LANs and MGCP does not have any method to associate the mobile terminal to the connection. Since MGCP typically deals with the fixed connection, MGCP does not describe mobile endpoints to set up the traffic connections to a call.

Thus, it is desirable to have a system and a method for transmitting CDMA calls including voice and data over a communication pathway with a higher bandwidth. It is further desirable to have a CDMA system that handles the transmission of calls, especially data calls, without the inherent difficulties of using a variety of transmission protocols for the same call. A need further exists for improved and less costly system which improves efficiency and the transmission rate and time of calls between a mobile unit and a base station and between base stations and a base station controller and between adjacent base stations.

SUMMARY OF INVENTION

The present invention is directed to a system and a method for providing an enterprise in-building or campus-wide IP based code division multiple access (CDMA) wireless system. The present invention is capable of handling both voice and data transmission over an internet protocol local access network within the CDMA system without the inherent delays and signal quality degradation encountered by conventional CDMA systems.

Embodiments of the invention include a system for linking or mapping a call in EIA/TIA –634 specification with a corresponding media gateway control protocol (MGCP) connection. The present invention provides a virtual circuit identity code (VCIC) as a linkage between EIA/TIA – 634 wireless siganling and media gateways control for a mobile terminal in a call agent to base station interface in a packet based network. VCIC includes a base station identifier and a virtual traffic path identifier (VTP id) to uniquely identify the traffic path with the enterprise network under a call agent.

The invention further includes an integrated wireless internet base station (WIBS) which is connected to the internet and an existing networking infrastructure within an office building or campus. The wireless base station utilizes known ethernet transmission protocols to transmit data over an ethernet back-bone to various wireless communication devices within a building. The wireless base station further includes a call processing module which is capable of determining whether a call originating from or received by the base station to and from a communication unit is either a voice or a data call.

The WIBS also integrates the base station control functions of the prior art to reduce call setups between a communication unit and the WIBS, and call handoffs between multiple WIBS. The WIBS further provides two functional logicall implementation of a signaling gateway and a media gateway for communicating to a call agent utilizing the EIA/TIA –634 protocol and MGCP protocol respectively.

The WIBS also includes an ethernet protocol interface module to enable it communicate over the ethernet back-bone and communicates over the back-bone and the internet using known ethernet and IP protocols. Since the ethernet back-bone uses a communication protocol different from the communication units, data received by the base station is packetized during processing into a format compatible with the ethernet transmission protocol of the ethernet back-bone and also to the internet.

The invention further includes a gateway which includes formatting logic to reformat data generated by the base station over the ethernet back-bone into a format compatible with the public switch network. A router is also connected to the ethernet back-bone to allow the WIBS send and receive data over the internet or an intranet.

The present invention further includes media processing logic which allows multiple WIBS in the system to communicate with each other during a soft handoff of communications between a mobile unit and a WIBS. By enabling adjacent WIBS to communicate during a soft handoff, the present invention reduces the time it takes to implement soft handoffs in a CDMA system and further reduces potential data loss due to such handoffs.

The present invention further provides an implementation advantage over the prior art by allowing inter network communication between the wireless office communication system of the present invention and other mobile networks on the public land mobile network. The inter-networking communication of the present invention is implemented over an IP LAN using the ethernet transport protocol of UDP/IP or TCP/IP transport protocol via an ethernet interface to the ethernet back-bone of the system. The use of the ethernet interface is less costly than the prior art and further allows easy and flexible connectivity to existing in-office, building or campus networks.

These and other objects and advantages of the present invention will no doubt become obvious to those of ordinary skill in the art after having read the following detailed description of the preferred embodiments which are illustrated in the various drawing figures.

BRIEF DESCRIPTION OF THE DRAWINGS

The accompanying drawings, which are incorporated in and form a part of this specification, illustrates embodiments of the invention and, together with the description, serve to explain the principles of the invention:

Prior Art Figure 1 is a block diagram of a conventional code division multiplex access (CDMA) system;

Prior Art Figure 2 is a block diagram of an implementation of a prior art enterprise CDMA system;

Figure 3 is a block diagram of a CDMA network protocol interface on an internet protocol LAN;

Figure 4 is a block diagram of an embodiment of a wireless CDMA communication system of the present invention; and

Figure 5 is a block diagram of an embodiment of the call message flow of the present invention.

DESCRIPTION OF THE PREFERRED EMBODIMENTS

Reference will now be made in detail to the preferred embodiments of the invention, examples of which are illustrated in the accompanying drawings. While the invention will be described in conjunction with the preferred embodiments, it will be understood that they are not intended to limit the invention to these embodiments.

On the contrary, the invention is intended to cover alternatives, modifications and equivalents, which may be included within the spirit and scope of the invention as defined by the appended claims. Furthermore, in the following detailed description of the present invention, numerous specific details are set forth in order to provide a thorough understanding of the present invention. However, it will be obvious to one of ordinary skill in the art that the present invention may be practiced without these specific details. In other instances, well known methods, procedures, components, and circuits have not been described in detail as not to unnecessarily obscure aspects of the present invention.

The invention is directed to a system, an architecture, subsystem and method to manage a wireless CDMA data communication in a way superior to the prior art. In accordance with an aspect of the invention, a base station allows CDMA call coverage within a building without requiring a dedicated and a lengthy end-to-end transmission.

In the following detailed description of the present invention, a system and method for a wireless internet protocol based communication system is described. Numerous specific details are not set forth in order to provide a

thorough understanding of the present invention. However, it will be recognized by one skilled in the art that the present invention may be practiced without these specific details or with equivalents thereof.

Generally, an aspect of the invention encompasses providing an integrated wireless internet protocol based in-building or campus-wide CDMA communication system which provides a wide range of voice, data, video and other services in conjunction with a private branch exchange interfaced to the Public Switched Telephone Network (PSTN) and the Public Land Mobile Network (PLMN). The invention can be more fully described with reference to Figures 3 through 5. Figure 3 is a functional illustration of the wireless system of the present invention. Wireless Office Solution system 300 (WOS) comprises, one or more mobile or wireless communication units 301-303, an enterprise wireless base station (WIBS) 310, a Call Agent 320 coupled to an ethernet backbone of the LAN 311 and the public switch telephone network gateway 330 (PSTN) .

Although the embodiment described above has been described with reference to one WIBS, the present invention is adaptable to handle one or more WIBS.

WOS 300 preferably is adapted to function with a code division multiplex access (CDMA) wireless technology. However, the present invention is adaptable equally to a time division multiple access (TDMA) system and other applicable wireless technologies.

Still referring to Figure 3, WIBS 310 is a IP based system which enables WOS 300 to take advantage of existing networking infrastructure in an office building or a similar environment to transmit wireless calls from the mobile units

to other wireless devices on the network, internet or to the PSTN. WIBS 310 includes switching functions to process traffic from various sources such as voice and data for delivery over the ethernet back-bone. Integration of base station controller and mobile switch controller functions enables WIBS 310 manage and coordinate radio resources to effect operations such as call origination, terminations and handoffs.

WIBS 310 further provides interface between a CDMA PCS or a cellular mobile communication system to enhance mobility within a wireless office environment covering hot spots or dead spots traditional public cellular or PCS networks such as on-campus, or the load etc. could not address.

WIBS 310 is coupled to the ethernet back bone preferably through a 10/100 base-T interface and related software stack to handle data burst on the LAN that traditional CDMA system could not handle. WIBS 310 receives and sends data to and from cellular regions to other subscription units in the WOS. WIBS 310 further receives radio signals from mobile units and packetizes the contents of the signals into data packets that are delivered over the ethernet back-bone to various destinations such as the PSTN and the internet.

Still referring to Figure 3, WOS 300 further includes a wireless Call Agent 320 which couples to ethernet back-bone 301 to provide call message handling to mobile units and other wireless devices connected to LAN 301. Call Agent 320 couples to WIBS 310 to provide mobile station controller like functions to WIBS 310. In the preferred embodiment wireless communication signals transmitted between WIBS 310 and Call Agent 320 are adaptable to EIA/TIA-634

communication specifications and media gateway control protocol (MGCP) specification.

Call Agent 320 further communicates with WIBS 310 via a media gateway communication protocol signal lines 302 to handle the transmission of media call functions between mobile units within WOS 300 and the public phone network system. In the preferred embodiment of the present invention, Call Agent 320 integrate mobile switch controller functionality to enable Call Agent 320 manage calls received by WOS 300.

Referring still to Figure 3, gateway 340 is coupled to the ethernet back-bone 311 to receive converted voice signals with WOS 300 from WIBS 310 for delivery to the PSTN. In the present invention gateway 340 preferably is a PSTN or Trunk gateway manufactured by Cisco® systems.

Referring to Figure 4, a functional block diagram of the wireless internet base station is illustrated WIBS 310. The invention shown in Figure 4 includes the WIBS 310, a Call Agent 340 and PSTN gateway 350.

The WIBS 310 comprises a signaling gateway logic 315 and a media gateway logic 320. Signaling gateway logic 315 is coupled to the Call Agent 340 via EIA/TIA –634 signal path to provide communications between the mobile terminals and the Call Agent. Signal gateway logic 315 couples the WIBS 310 to the mobile terminals within the system via radio signaling channels. WIBS 310 further includes logic for creating a virtual traffic path for linking call signals identifiers from signaling gateway logic 315 to a corresponding identifiers in media gateway logic 320.

Media gateway logic 320 also couples the WIBS 310 to mobile terminals via radio traffic channels and to PSTN gateway 350 via a Real-time transport protocol (RTP) signal path to provide a communication path between the WIBS 310 and the public network. Media gateway logic 320 further couples to the Call Agent 340 via MGCP path 302 to provide communication between WIBS 310 and the Call Agent utilizing the media gateway controller protocol (MGCP).

MGCP 320 is designed to interface a media gateway controller and media gateway. The protocol supports a centralized call model. The media gateway controller is Call Agent in MGCP terminology and the media gateway can be either different types of VoIP gateways (residential, trunking, corporate, etc.), network access servers or even voice over ATM gateways. MGCP is a master/slave protocol. It uses other protocols to fulfill its requirements, such as the session description protocol which is used to describe the media aspects of a phone call. Media gateway logic 320 provides WIBS 310 with voice-over IP (VoIP) functionality to enable WIBS 310 to support VoIP services over LAN 301.

In the embodiment shown in Figure 4, during the signal processing of mobile terminal's originated call or a land originated call, the SG 315 receives a request from Call Agent 340 to allocate the mobile to a dedicated traffic channel. The request includes the identification (id) of the VCIC that represents the id of the virtual traffic path of the call. SG 315 processes the request by requesting the MG 320 to allocate a traffic channel and passes the id of VCIC received from Call Agent 340. MG 320 then sends commands to the mobile unit to start using the virtual traffic channel.

The VCIC includes a base station identifier and a virtual traffic path identifier which allows the WIBS 310 and Call Agent 340 to uniquely identify the virtual traffic path within the enterprise network under Call Agent 340. More specifically, the base station identifier is adapted to locate the media gateway and the virtual traffic path identifier is adapted to locate a specific virtual path within the base station.

A traffic path is created between the base station and the mobile unit. The SG 315 responds to the Call Agent that the mobile is on a dedicated traffic channel. The Call Agent then sets up a media path between PSTN gateway 350 and MG 320. Setting up the media path by the MG 320 is performed using MGCP, and the Call Agent 340 invokes MGCP commands to MG 320. Since multiple calls are processed simultaneously, it is necessary for the Call Agent 340 to indicate which mobile terminal that the media stream (using RTP) should be set up in that MGCP command.

Figure 5 is a block diagram illustration of one embodiment of a call message flow on the present invention. A call message in the present invention is initiated by mobile terminal 501 by sending a call origination signal 506 to base station 505. Signaling gateway 503 in base station 505 processes the call origination signal 506 and transmits the processed request to call agent 510.

The base station 505 then sends a signal receipt acknowledgment signal 516 to the mobile station 501 indicating the receipt and processing of the call origination request. After receiving the channel request from the signaling gateway 503, Call Agent 510 transmits a channel request signal 519 to the signal

gateway 503 requesting allocation to the mobile station, a dedicated traffic channel, e.g., message X. Message X 518 includes the id of VCIC that represents the id of the traffic path of the call.

The signal gateway 503 then processes the channel request by requesting the media gateway 502 to allocate a traffic channel signal e.g., channa 526, passes the id of VCIC received from the Call Agent and instructs the mobile station 501 to begin using the dedicated traffic channel.

During this process, the traffic path between the base station 505 and the mobile station 501 is established subsequent to establishing of the mobile station and base station communication path, the signaling gateway 503 then responds to the calll agent 510 that the mobile station 501 is on a dedicated traffic channel via traffic channel signal 525 (e.g., message y).

Upon receiving the traffic signal channel assignment complete signal 525, the call agent initializes the set up of a media communication pathway between PSTN gateway 515 and the media gateway 502 utilizing an MGCP hand-shake protocol via message signal 526 (Z) to enable the mobile terminal to begin transmitting to the PSTN. MG 502 then acknowledges receipt of message signal Z 526 by transmitting a MGCP signal success signal via signal 528 from MG 503 to Call Agent signaling initiator 540. When the Call Agent signal initiator 540 receives signal 528, an RTP traffic path is established to allow the mobile unit 501 to communicate with Call Agent 510.

Upon establishing the RTP path, PSTN user call answer 550 will start ringing at the PSTN end of the system. PSTN user call answer unit 550 then

transmits a message signal (e.g. Z) to the mobile unit 501 via service negotiator 535 utilizing the MGCP handshake protocol. The MGCP handshake protocol will include a VCIC code which established a virtual traffic path to allow the mobile unit 501 to communicate with the PSTN user answering a call from PSTN user call answer unit 550. Once communication link is established between the mobile unit and PSTN user call answer unit 550, the mobile unit will begin transmitting via media signal line 555.

As shown in Figure 5, the mobile unit 501 communicated to MG 503 using the IS95 traffic protocol and MG 503 communicates messages received from mobile unit 501 to PSTN gateway 515 using MGCP protocol via signal 555.

The foregoing descriptions of specific embodiments of the present invention have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the invention to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teaching. The embodiments were chosen and described in order to best explain the principles of the invention and its practical application, to thereby enable others skilled in the art to best utilize the invention and various embodiments with various modifications are suited to the particular use contemplated. It is intended that the scope of the invention be defined by the Claims appended hereto and their equivalents.